



**MITSUBISHI
ELECTRIC**

PLK-G2008H With Top and Bottom Hot Knife Trimmer

PLK-G2008H-BTRM With Bottom Hot Knife Trimmer Only



SPECIFICATIONS

Stitch Type	Single Needle Lockstitch	Hook	Barrel Type Shuttle/ Size 33 Bobbin
Max. Number of Sewing Patterns Possible	Internal Memory (512) USB (depends on memory size)	X/Y Drive	Timing Belt
Sewing Area	(X) 8" x (Y) 3 $\frac{1}{8}$ " (200mm x 80mm)	Needle	Schmetz 794 Size 26 (Standard)
Max. Sewing Speed	700 RPM	Work Holder Lift	Max. 25mm
Sewing Speed Selection	200~700 RPM (10 Steps Variable)	Presser Foot Lift	Max. 25mm
Feeding System	Intermittent	Pattern Input	Touch Screen (PLK-G-PAL)
Stitch Length	0.1~20.0mm	Drive Motor	Limi-Servo (550 Watts)
Pattern Storage	Internal Memory or External USB	Power	220 Volt 3 Phase or Single Phase
Max. Number of Stitches	20,000 Per Pattern	Power	110 Volt (Optional)
Scale Up/Scale Down	10~200% for X and Y Axis	Clamp (Air)	Single or 2-Stage
Presser Foot	Air Controlled	Total Weight (Net)	172kg

NOTE: Sewing speed may be limited by the type of operation, material, or clamp weight.