

PLK-G1010



SPECIFICATIONS

Stitch Type	Single Needle Lockstitch	Hook	Shuttle/Large/Size R Bobbin
Max. Number of Sewing Patterns Possible	Internal Memory (512) USB (depends on memory size)	X/Y Drive	Timing Belt
Sewing Area	(X) 4" x (Y) 4" (100mm x 100mm)	Needle	135x17 Size 18 (Standard)
Max. Sewing Speed	2800 RPM	Work Holder Lift	Max. 25mm
Sewing Speed Selection	200~2800 RPM (10 Steps Variable)	Presser Foot Lift	Max. 15mm
Feeding System	Intermittent or Continuous	Pattern Input	Touch Screen (PLK-G-PAL)
Stitch Length	0.1~20.0mm	Drive Motor	Direct Drive (750 Watts) (1HP)
Pattern Storage	Internal Memory or External USB	Power	220 Volt 3 Phase or Single Phase
Max. Number of Stitches	20,000 Per Pattern	Power	110 Volt (Optional)
Scale Up/Scale Down	10~200% for X and Y Axis	Clamp (Electric)	Single Stage
Presser Foot	Stepping Motor Controlled	Total Weight (Net)	133kg

NOTE: Sewing speed may be limited by the type of operation, material, or clamp weight.